

**Sha Tin Town Hall - Auditorium** Basic Technical Information

	Basic Technical Information			
	V. 2022.5.16		Page 1 of 1	
Performing Arts Division - Technical Support Unit	Seats	1372 - stalls 589, upper stalls 443, balcony 340		
Sha Tin Town Hall			EISA799587	
No. 1, Yuen Wo Road Sha Tin,	Proscenium	Width	12.00 - 16.00 m	
NT, HK		Height	6.00 - 8.84 m	
Phone	Stage Width	Centreline to Stage right under gallery	11.53 m 11.48 m	
852-2694 2509		Centreline to Stage left under gallery Between fly floors	23.00 m	
		Centreline to Stage right under gallery (off stage)	14.70 m	
Fax		Centreline to Stage left under gallery (off stage)	12.70 m	
852-2693 4878	Stage Height	Clear under fly floor	9.07 m	
CONTACTS		Clear under grid	24.74 m	
CONTACTS		Maximum flying bar height (manual)	23.75 m	
Winnie POON	Stage Depth	Rear of proscenium to clear under gallery	16.05 m	
Senior Manager (NTE) Venue		Rear of proscenium to stage edge on CL	2.35 m	
Direct Line	Concert Layout	Medium (Orchestra of 80 members)	171.42 m <sup>2</sup>	
852-2694 2505		Large (Orchestra up to 130members)	229.73 m <sup>2</sup>	
Leo LEUNG	Stage Surface	Flat / Danish Oak (no nailing direct on stage floor	)	
Manager (NTE /	Side Stage	15.00 x 14.00 x 9.07m (W x D x H)		
Operations 1)	Rear Stage	19.00 x 8.16 x 3.82m (W x D x H)		
<i>lkmleung@lcsd.gov.hk</i> Direct Line	Тгар	None		
852-2694 2506	Orchestra pit	20.53 x 4.53 x 2.45m (W x D x H) max., height to audience level 2.12 m Pit 91.5 m <sup>2</sup> with a loss of 73 seats		
Dennes KWAN It is				
Manager (NTE) Flying System 40 double purchase counterweights, SWL 5		40 double purchase counterweights, SWL 500kg,		
dyykwan@lcsd.gov.hk bars 20.00m long				
	352-2694 2571 Stage Manager Working corner at DSL - two-ring intercom system,			
	Desk	CCTV, show relay system and dressing room paging		
	Wardrobe	Running wardrobe at M level - washing machines, dryers, steamers,		
GENERAL		irons & boards		
<u>SET-UP</u>	Dressing Rooms	13 dressing rooms at M level for around 100 persons, 6 rooms with		
The Auditorium		private toilet and shower, quick change rooms at DSL and DSR ETC Gio Console, 140 channels, located in control room at rear balcony.		
operates on a	Electrics	Full complement of luminaries		
'bare-walls' touring		Follow spots x 2, Lighting tower x 10 units (2m tall)		
policy. That is, all		Additional power: 100A x 3phase at side stage left and right,		
equipment is		63A x 3phase, 32A x 3 phase at side stage left		
normally set-up and struck within the	Sound	DiGiCo SD7 Quantum with 56 Inputs and 8 Outputs, in control room		
booking period.		at rear stalls		
Hirers are reminded		Dual channel speakers on sides of proscenium		
to allow sufficient	Droigotion	Variety of microphones, wireless microphones		
preparation time to	Projection Storage Space	Panasonic PT-RQ35K Multimedia Projector, 30,000 ANSI Lumens 116 m <sup>2</sup> store area between side stage, clear height 9.00m		
hang theatre	Get-in	Loading platform at 0.75m off ground,		
masking, rig all	Oet-III	via cargo lift $3.10 \times 7.25 \times 3.60$ m (W x D x H)		
overhead stage	Crossover	Rear of stage and M level		
lighting and setup	Equipment	Orchestra risers, choir risers, podium,		
sound system. Black Masking - borders, legs, black drop, half tabs,		bs,		
INFORMATION	1	2 Cycloramas 19.50 x 11.00m (W x H), House Cu		
Full technical		Aerial lift (14.1m max. height),		
drawings available	<u></u>	Dance Flooring, Carpets (For Chinese Opera)		
Other Facilities Sub-studio for broadcasting in stalls level				
	Instruments	Concert grand pianos, 1 set of timpani, Chinese o	frum	